

TOWER SCREEN SYSTEM

Got everything covered

2 Merezhna str, Bila Tserkva,
Kyiv region, 09109, Ukraine
Tel./Fax.: +38 044 2774789
e-mail: info@mag-cinema.com
www.mag-cinema.com



SOUNDS
AS DESIGNED



TOWER SCREEN SYSTEM

Modular screen speaker solution

TOWER SCREEN SYSTEM is the next generation modular screen system for top-class cinema halls, which establishes new standard of sound clarity, presence, and performance.

TOWER SCREEN SYSTEM is designed specifically to fit into different cinema hall sizes while delivering uniform performance in each and every installation.

TOWER SCREEN SYSTEM is based on set of easily connectable acoustic cabinets, complete with the rigging and flying hardware.

Acoustic cabinets are carefully designed to merge into unified system, regardless of the actual array size. This allows to deliver the signature sound performance into any cinema hall of any size.

Simple and effective rigging system features all-purpose elements allowing to assemble the **TOWER SCREEN SYSTEM** into flown clusters or ground stacks.

Modular solution not only cuts down the installation time, but also allows for optimal stock with fewer components to worry about while designing the particular system.



TOWER SCREEN SYSTEM

TECHNICAL SPECIFICATIONS

TSS Subwoofer	Tower-B	
Frequency response (-3 dB)	42 - 200 Hz	
Max SPL (peak)	135 dB (calculated)	
Sensitivity (1W/1m)	98 dB	
LF Transducer	2x12"	
Impedance	4 Ohm	
Nominal power (1)	1200 W	
Program power	2400 W	
Peak power	4800 W	
Connectors	Barrier strip terminal	
Mounting options	Integrated rigging hardware	
Dimensions (WxHxD)	800x386x447 mm	
Net weight	38,2 kg	
Shipping weight	41,4 kg	
TSS MID-HI Module	Tower-T4	Tower-T8
Frequency response (±3 dB)	100-22000 Hz	
Max SPL (peak)	131 dB	
Sensitivity (1W/1m)	98 dB MID / 113 dB HI	
LF Transducer	4x6"	
HF Transducer	2x1"	
Horizontal coverage	90 deg	
Vertical splay angle	4 deg	8 deg
Impedance	8 Ohm MID / 16 Ohm HI	
Nominal power (1)	520 W MID / 100 W HI	
Program power	1040 W MID / 200 W HI	
Peak power	2080 W MID / 400 W HI	
Connectors	Barrier strip terminal	
Mounting options	Integrated rigging hardware	
Dimensions (WxHxD)	456x368x287 mm	456x376x292 mm
Net weight	21,6 kg	
Shipping weight	24,0 kg	

DIMENSIONS

